

SAFETY DATA SHEET

1. Identification

Product identifier Car Shine 2:1 HS Clear Coat LV
Other means of identification
Product Code SSC2101
Recommended use Automotive/Industrial Clear Coat

Manufacturer/Importer/Supplier/Distributor information Manufacturer

Company name TOP QUALITY TRADING LLC
PO BOX 64
WILMINGTON DE 19899
Address
Telephone 302-509-9460
E-mail info@tqtusa.com
Contact person Chemtrec
Emergency phone number 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 2
	Acute toxicity, dermal	Category 2
	Acute toxicity, inhalation	Category 2
	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child)	Category 1B
	Specific target organ toxicity, single exposure	Category 3
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Hazardous to the aquatic environment, long-term hazard	Category 2
Label elements	Not classified.	



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Toxic if swallowed. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Response Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor.

Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage In case of fire: Use appropriate media to extinguish. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information 22% of the mixture consists of component(s) of unknown acute dermal toxicity. 65% of the mixture consists of component(s) of unknown acute inhalation toxicity. 26% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 26% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Ingredient Name	CAS Number	% by Weight
p-Chlorobenzotrifluoride	98-56-6	≥25 – ≤50
Acetone	67-64-1	≥25 – ≤50
n-Butyl Acetate	123-86-4	≤3
Methyl pentamethylpiperidyl sebacate	82919-37-7	≤1

Bis(pentamethyl-4-piperidyl)sebacate	41556-26-7	≤1
Dibutyltin Dilaurate	77-58-7	<1
Xylene, mixed isomers	1330-20-7	≤0.3
Other components below reportable levels		

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.
Environmental precautions	

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation.
--------------------------------------	--

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse.

Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to

8. Exposure controls/personal protection

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency

Ingredient	CAS	OSHA TWA	OSHA STEL	ACGIH TWA	ACGIH STEL
Acetone	67-64-1	1000 ppm / 2400 mg/m ³	–	250 ppm	500 ppm
p-Chlorobenzotrifluoride	98-56-6	Not established	Not established	Not established	Not established
n-Butyl Acetate	123-86-4	150 ppm / 710 mg/m ³	200 ppm / 950 mg/m ³	150 ppm	200 ppm
Methyl pentamethylpiperidyl sebacate	82919-37-7	Not established	Not established	Not established	Not established
Bis(pentamethyl-4-piperidyl)sebacate	41556-26-7	Not established	Not established	Not established	Not established
Dibutyltin Dilaurate	77-58-7	0.1 mg/m ³ (as Sn)	0.2 mg/m ³ (as Sn)	0.1 mg/m ³	0.2 mg/m ³
Xylene, mixed isomers	1330-20-7	100 ppm / 435 mg/m ³	150 ppm / 655 mg/m ³	20 ppm	Not established

Appropriate engineering controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Clear.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	55°C (131°F) estimated
Flash point	Closed cup: -20°C (-4°F) [Pensky-Martens Closed Cup]
Evaporation rate	5.6 (butyl acetate = 1)
Flammability (solid, gas)	Flammable liquid.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.9 % estimated
Flammability limit - upper (%)	12.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	24 kPa (180 mm Hg) estimated
Vapor density	2 [Air = 1]
Relative density	1.12
Solubility (ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic (40°C (104°F)): <20.5 mm ² /s (<20.5 cSt)
Other information	
Density	1.11 g/cm ³
Flammability class	Flammable IB estimated
Percent volatile	100 %
Specific gravity	Not available.

VOC

0.91 lbs/gal Material

109.5 g/l Material

250 g/l Regulatory

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible
Incompatible materials	Acids. Strong oxidizing agents.
Hazardous decomposition	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes

Inhalation Toxic if inhaled. May cause damage to organs by inhalation. May cause damage to organs
Headache. Nausea, vomiting.

Skin contact Harmful in contact with skin. Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Toxic if swallowed.

Physical, Chemical and Toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Toxic if inhaled. Toxic if swallowed. Harmful in contact with skin. Narcotic effects.

Component	Species	Test Results
Acetone (67-64-1)		
Oral LD50	Rat	5,800–7,800 mg/kg
Dermal LD50	Rabbit	20,000 mg/kg
Inhalation LC50	Rat	50,100 mg/m ³ (8 hrs)
p-Chlorobenzotrifluoride (98-56-6)		
Oral LD50	Rat	>2,000 mg/kg
Dermal LD50	Rabbit	>2,000 mg/kg
Inhalation LC50	Rat	>6,000 ppm (4 hrs)
n-Butyl Acetate (123-86-4)		
Oral LD50	Rat	10,760 mg/kg
Dermal LD50	Rabbit	>5,000 mg/kg
Inhalation LC50	Rat	2,000 ppm (4 hrs)
Methyl pentamethylpiperidyl sebacate (82919-37-7)		
Oral/Dermal/Inhalation	–	Data not available
Bis(pentamethyl-4-piperidyl)sebacate (41556-26-7)		
Oral/Dermal/Inhalation	–	Data not available
Dibutyltin Dilaurate (77-58-7)		
Oral LD50	Rat	175 mg/kg
Dermal LD50	Rabbit	1,100 mg/kg
Inhalation LC50	Rat	0.2 mg/L (4 hrs)
Xylene, mixed isomers (1330-20-7)		
Oral LD50	Rat	3,523 mg/kg
Dermal LD50	Rabbit	>1,700 mg/kg
Inhalation LC50	Rat	6,350 ppm (4 hrs)
Methyl n-Amyl Ketone (2-Heptanone) (110-43-0)		
Oral LD50	Rat	1,600 mg/kg
Dermal LD50	Rabbit	>2,000 mg/kg
Inhalation LC50	Rat	>7,000 ppm (4 hrs)

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.
Serious eye damage Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging the unborn child.

Specific target organ toxicity May cause damage to organs. May cause drowsiness and dizziness

–

Single exposure

Specific target organ toxicity Causes damage to organs through prolonged or repeated exposure

–

Repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.






Component	Species	Test Type	Result	Duration	Effect
	Daphnia magna	EC50 (48h)	8,800 mg/L	48h	Population
	Mycrocystis aeruginosa	NOEC (8d)	530 mg/L	8d	Reproduction
	Rainbow trout (<i>O. mykiss</i>)	LC50	6,070–15,000 mg/L	96h	Mortality
p-Chlorobenzotrifluoride (98-56-6)	Fathead minnow	LC50 (96h)	13.5 mg/L	96h	Mortality
	Daphnia magna	EC50 (48h)	3.68 mg/L	48h	Population
n-Butyl Acetate (123-86-4)	Rainbow trout (<i>O. mykiss</i>)	LC50 (96h)	18 mg/L	96h	Mortality
	Daphnia magna	EC50 (48h)	44 mg/L	48h	Population
Dibutyltin Dilaurate (77-58-7)	Calanoid copepod (<i>Acartia</i>)	LC50 (48h)	0.12 mg/L	48h	Mortality
	Algae (<i>Skeletonema costatum</i>)	EC50 (72h)	0.03 mg/L	72h	Growth inhibition
	Threespine stickleback (<i>G.</i>)	NOEC (42d, larvae)	5 µg/L	42d	Population
Xylene, mixed isomers (1330-20-7)	Rainbow trout (<i>O. mykiss</i>)	LC50 (96h)	13.5 mg/L	96h	Mortality
	Daphnia magna	EC50 (48h)	3.82 mg/L	48h	Population
Methyl n-Amyl Ketone (2-Heptanone, 110-43-0)	Zebra fish (<i>Danio rerio</i>)	LC50 (96h)	143 mg/L	96h	Mortality
	Daphnia magna	EC50 (48h)	197 mg/L	48h	Population
Methyl pentamethylpiperidyl sebacate (82919-37-7)	Daphnia magna	EC50 (48h)	<1 mg/L	48h	Population
	Fish (unspecified)	LC50 (96h)	<1 mg/L	96h	Mortality
Bis(pentamethyl-4-piperidyl)sebacate (41556-26-7)	Daphnia magna	EC50 (48h)	<1 mg/L	48h	Population
	Fish (unspecified)	LC50 (96h)	<1 mg/L	96h	Mortality

Persistence and degradability No data is available on the degradability of this product.
 Mobility in soil No data available.
 Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow
Local disposal regulations Dispose in accordance with all applicable regulations.
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste
Waste from residues unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal
Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after

14. Transport information

Detail	DOT (U.S.)	TDG (Canada)	Mexico	IATA (Air)	IMDG (Sea)
UN Number	UN1263	UN1263	UN1263	UN1263	UN1263
Proper Shipping Name	Paint or Paint Related Material	Paint or Paint Related Material	Pintura o material relacionado	Paint or Paint Related Material	Paint or Paint Related Material
Transport Hazard Class	3 (Flammable) 	3 (Flammable) 	3 (Inflamable) 	3 (Flammable) 	3 (Flammable) 
Packing Group	II	II	II	II	II
Environmental Hazards	Not indicated	Not indicated	Not indicated	May be hazardous to environment	Marine Pollutant
Additional Information	49 CFR §172.101; ERG #128	TDG Schedule 1; ERAP not required	NOM-002-SCT; Emergency Sheet required	IATA DGR PI 355; ERG #128	IMDG Code 3.2; EmS F-E, S-E; Stowage Category A

Local disposal regulations: Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments Not Available

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
 Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)
 Not regulated.

SARA 304 Emergency release notification
 Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
 Not listed.

US state regulations**US. California Proposition**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10/5/2025
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.